MANHATTAN
BRINGING COMPUTERS TO LIFE



Serial/Parallel Combo PCI Card

Two Serial DB9 + One Parallel DB25 External Ports

Model
158251

Use a single PCI slot to add two serial ports and one parallel port.

Compatible with most RS232 peripherals, the MANHATTAN® Serial/Parallel Combo PCI Card with two external serial DB9 ports is an ideal solution for attaching two serial devices — modems, barcode scanners, printers and more — and a parallel DB25 port through a single PCI card and two open rear expansion slots. Its two high-speed 16C550 UART serial DB9 Com ports fully support PCI IRQ sharing even if accessed simultaneously to help save valuable resources for other expansion cards. The DB25 port with Enhanced Parallel Port (EPP), Standard Parallel Port (SPP) and Enhanced Capability Port (ECP) help support the faster transfer of large amounts of data.

Easy Installation

Windows 2000/XP/Server 2003/Vista/7 32/64-bit compatibility, Plug and Play capability and automatic IRQ and IO address selection make installation easy to help avoid configuration conflicts with other devices.

Lifetime Warranty

Strict manufacturing standards ensure the highest quality in all MANHATTAN products. All items carry a full Lifetime Warranty — the strongest quality commitment anyone can make.

LIFETIME WARRANTY



LIFETIME WARRANTY

Model
158251

Features

- Adds two external high-speed 16C550 UART serial DB9 Com and one parallel DB25 external ports to desktop computers
- Maximum 115.2 kbps throughput on each serial port
- Up to 1.5 MBps parallel throughput
- Universal bus power design for 5 V and 3.3 V
- Parallel DB25 port supports Enhanced Parallel Port (EPP), Standard Parallel Port (SPP) and Enhanced Capability Port (ECP)
- Fully supports PCI IRQ sharing
- Automatically selects IRQ and IO address
- Lifetime Warranty

Specifications

STANDARDS AND CERTIFICATIONS
- CE
- FCC
- RS-232c
- PCI 2.3
- RoHS
- WEEE

PORTS
- (2) serial DB9 male connections; maximum 115.2 kbps throughput on each port (256 byte FIFO)
- (1) parallel DB25 female connections; maximum 1.5 MBps throughput (256 byte FIFO)
- MosChip 9865 chipset
- Supports EPP), Standard Parallel Port (SPP) and Enhanced Capability Port (ECP)

BUS
- PCI 2.3 32-bit, 33 MHz
- Supports 32-bit PCI slot
- 5 / 3.3 V bus power

PHYSICAL
- Dimensions:
  - Controller card: 124 x 122 x 23 mm (4.9 x 4.8 x 0.9 in.)
  - Serial expansion plate, including cable: 181 x 122 x 23 mm (7.1 x 4.8 x 0.9 in.)
- Weight: 96.3 g (3.4 oz.)

SYSTEM REQUIREMENTS
- Windows 2000/XP/Server 2003/Vista/7 32/64 bit
- (2) available punch-out expansion and (1) PCI slots

PACKAGE CONTENTS
- Serial/Parallel Combo PCI Card with expansion plate
- User manual and driver CD

For more information on MANHATTAN products, consult your local dealer or visit **www.manhattan-products.com**.

MANHATTAN
BRINGING COMPUTERS TO LIFE

Copyright © MANHATTAN

All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.